



AS

AUTOMATIC UNIFORM SIDEDRIVE


The BestPack™ AS Series is a fully automatic carton sealer designed to meet the needs of uniform in-line carton closure applications. Designed with a solid four column support structure and using dual motor side belt technology, the AS closes all four top flaps and seals the top & bottom of the carton, using 60 PSI and 5 SCFM of air.

NOW EQUIPPED WITH OUR DATA ADVANTAGE SYSTEM!*

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



FULLY AUTOMATIC



UNIFORM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements

UP TO 57 CPM

Speed


60 PSI, 5 SCFM

Air Requirements

650-760 LBS

Shipping Weight

CARTON RANGE



Length (min. - max.)
(8.0" - 27.5")

Width (min. - max.)
(6.0" - 20.0")

Height (min. - max.)
(5.5" - 20.0")

Specifications based on AS22-2

STANDARD FEATURES

- Adjustable Bed Height from 22.5" to 30.0"
- Width/Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Interlock Safety Gates in the Kicker Station
- Upper Side Compression Unit
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Capable of Interchanging 2" or 3" Tape Heads
- In-line Automatic Top Flap Folding
- Electrical On/Off Box can be Mounted on Either Side of Carton Sealer
- Exclusive Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm



DATA ADVANTAGE SYSTEM COMES WITH:

- Low Tape/No Tape Monitoring
- Improved Electrical Efficiency
- Jam Detection
- Machine Performance Tracking and more features to improve your experience...

OPTIONS

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- VFD Motor Upgrade (Up to 150+ ft. per min.)
- Locking Heavy-Duty Casters
- Additional Safety Guarding Available
- Compatible Indexer: ARX Model

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine
Minimize downtime with BestPack's Spare Parts Kit.




INDEXER STATION

The indexer's function is to separate and time cartons going into the carton sealer.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)



ADDITIONAL SAFETY GUARDING

Add additional protective measures that prevent workplace injuries with additional safety gates around your equipment.

POPULAR AS MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE*** LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.****	SHIPPING WEIGHT (LBS)
AS12-2 2" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	500
AS12-2H** 2" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 57	500
AS12-3 3" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	500
AS12-3H** 3" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 57	500
AS22-2 2" Tape Head	(77.7") x (33.8") x (69.0")*	(8.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	585
AS22-2H** 2" Tape Head	(77.7") x (33.8") x (69.0")*	(8.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 57	585
AS22-3 3" Tape Head	(77.7") x (33.8") x (69.0")*	(8.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	585
AS22-3H** 3" Tape Head	(77.7") x (33.8") x (69.0")*	(8.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 57	585

Information subject to change without notice.

* Safety Gates are an Additional 20" Long
** High Speed
*** Outside Dimensions Only
**** Based on Customer Application



For more information please go to:
WWW.PAKTEKSYSTEMS.COM or call us at **905.673.7730**